

## MODELS

### Compaq MV5500 Color CRT Monitor

Part Number: 261599-002

UPC: 720591212148

## SPECIFICATIONS

<b>Tube Type</b>	Color, Conventional FST, Multi-frequency			
<b>Picture Tube Size</b> (diagonal)	15-inch (38.1 cm)			
<b>Viewable Image Area</b> (diagonal)	13.8-inch (35.1 cm)			
<b>Trio Dot Pitch</b>	0.28 mm			
<b>Horizontal Dot Pitch</b>	0.24 mm			
<b>Horizontal Frequency</b> (kHz)	30 to 54 kHz			
<b>Vertical Frequency</b> (Hz)	50 to 120 Hz			
<b>Maximum Pre-set Resolution</b>	1024 x 768 @ 60 Hz			
<b>Preferred Flicker Free Resolution</b>	800 x 600 @ 85 Hz			
<b>Preset Graphic Modes</b>	1024 x 768	800 x 600	720 x 400	640 x 480
<b>Note:</b> All modes are non-interlaced unless specified otherwise.	@ 60 Hz	@ 85 Hz and 75 Hz	@ 70 Hz	@ 85 Hz, 75 Hz and 60 Hz
<b>User-Modes</b>	Yes, 4 modes			
<b>Anti-Glare/Anti-Static</b>	Yes			
<b>AssetControl</b>	Yes, supported			
<b>Plug and Play</b>	Yes			
<b>Icon Based On-Screen Display Controls</b>	Yes			
<b>User Controls</b>	<b>Brightness, Contrast</b>	Yes		
	<b>Size and Positioning</b>	Yes		
	<b>Pincushion</b> (barrel)	Yes		
	<b>Trapezoid</b>	Yes		
	<b>Parallelogram</b>	Yes		
	<b>Exit</b>	Yes		
	<b>Degauss</b>	Yes		
	<b>Factory Reset/Recall</b>	Yes		
	<b>Current Display Mode</b>	Yes		

## SPECIFICATIONS *(continued)*

<b>Approvals/Certifications</b>	<b>UL/CSA/CUL Approval</b>	Yes
	<b>ISO9241-3, -7, -8 VOT Guidelines Approval</b>	Yes
	<b>MPR-II Compliant</b>	Yes
	<b>FCC Approval</b>	Yes
	<b>Microsoft WHQL Certified</b>	Yes
	<b>CE</b>	Yes
	<b>Energy Star Compliant</b>	Yes
<b>Maximum Pixel Clock Speed</b>	70 MHz	
<b>Power Supply</b>	Universal; 100 to 240 V, 50 $\pm$ 3Hz and 60 $\pm$ 3Hz	
<b>Maximum Power Rating</b>	<=80 watts	
<b>Low Power Sleep Mode</b>	< 5 watts	
<b>Signal Cable</b>	15-pin miniature D-sub, attached, 5.9 feet (1.8 meter)	
<b>Dimensions (H x W x D)</b>	<b>Unpacked</b>	15.7 x 14.4 x 16.5 in (40 x 36.5 x 41.8 cm)
	<b>Packaged</b>	20.9 x 17.9 x 20.4 in (53 x 45.5 x 51.8 cm)
<b>Weight</b>	<b>Unpacked</b>	29 lb (13.15 kg)
	<b>Packaged</b>	37.4 lb (17.0 kg)
<b>Operating Temperature</b> (non-condensing)	50° to 95°F (10° to 35°C)	
<b>Operating Humidity</b> (non-condensing)	20% to 80%	
<b>Express Service</b>	Compaq Express Service offers 48-hour replacement with a new or refurbished Compaq monitor	
<b>Warranty</b>	One-year parts and labor, limited warranty. Certain restrictions and exclusions apply. For details, contact Compaq Customer Support at 1-800-OKCOMPAQ.	

## JBL PLATINUM SERIES SPEAKER SPECIFICATIONS

<b>On/Off/Volume Control and LED</b>	Yes, front panel of right speaker	
<b>Line Input Jack</b>	Yes (Digital Audio Port Input)	
<b>Sound Output</b>	3 watt RMS per channel @ 10% Total Harmonic Distortion (THD)	
<b>Frequency Response</b>	100 Hz to 20 kHz	
<b>Sound Pressure Level</b>	86 dB (1 watt/1 meter) averaged at 300, 400, 500, 600 Hz	
<b>Nominal Impedance</b> (3-inch Driver)	4 ohms	
<b>Speaker Weight</b>	<b>Right</b>	1.26 lb (572 g)
	<b>Left</b>	1.12 lb (506 g)
<b>Speaker Dimensions</b> (H x W x D)	9 x 3.3 x 4 in (22.86 x 8.38 x 10.16 cm) per speaker	
<b>Power Supply</b> (USA)	<b>Input</b>	120V, 60Hz, 25W
	<b>Output</b>	12V (DC), 1 amp
<b>Speaker Cable Lengths:</b>	<b>Audio Signal Cable</b>	6.23 feet (1.9 meter)
	<b>Right Speaker to Left Speaker</b>	5.9 feet (1.8 meter)
	<b>Power Adapter</b>	6 feet (1.83 meter)
<b>Cabinet and Grill Color</b>	Black	

Compaq, registered United States Patent and Trademark Office. Other product names mentioned herein may be trademarks and/or registered trademarks of their respective companies.  
 ©2001 Compaq Computer Corporation.